

LINERS FOR CORED WIRE



ROUND WOUND



'D' WOUND



FLAT WOUND

PART #	DESCRIPTION	WIRE SIZE	LENGTH	I.D.
415-35-082	GALVANIZED STEEL EXTENDED LIFE - 'D' WOUND FOR TORCHES ≤ 8'	.035" - .045"	9.5'	.075"
415-35-152	GALVANIZED STEEL EXTENDED LIFE - 'D' WOUND FOR TORCHES ≤ 15'	.035" - .045"	16.5'	.075"
415-35-252	GALVANIZES STEEL EXTENDED LIFE - 'D' WOUND FOR TORCHES ≤ 25'	.035" - .045"	26.5'	.075"
415-564-6	HIGH CARBON STEEL - 'D' WOUND FOR TORCHES ≤ 6'	1/16" - 5/64"	7.5'	.097"
415-564-10	HIGH CARBON STEEL - 'D' WOUND FOR TORCHES ≤ 6'	1/16" - 5/64"	11.5'	.097"
415-564-15	HIGH CARBON STEEL - 'D' WOUND FOR TORCHES ≤ 15'	1/16" - 5/64"	16.5'	.097"
415-564-25	HIGH CARBON STEEL - 'D' WOUND FOR TORCHES ≤ 25'	1/16" - 5/64"	27.0'	.097"
415-332-1	HIGH CARBON STEEL - FLAT WOUND FOR AUTO HEADS ≤ 1.5'	.078" - 3/32"	1.5'	.125"
415-332-6	HIGH CARBON STEEL - FLAT WOUND FOR TORCHES ≤ 6'	.078" - 3/32"	7.5"	.125"
415-332-15	HIGH CARBON STEEL - FLAT WOUND FOR TORCHES ≤ 15'	.078" - 3/32"	16.5'	.125"
415-332-25	HIGH CARBON STEEL - FLAT WOUND FOR TORCHES ≤ 25'	.078" - 3/32"	26.5'	.125"
415-332-153	GALVANIZED STEEL - ROUND WOUND - NO HEAT SHRINK	.078" - 3/32"	16.5'	.142"
415-332-154	GALVANIZED STEEL - ROUND WOUND FOR TORCHES ≤ 15'	3/32"	16.5'	.142"
415-332-158	HIGH CARBON STEEL - 'D' WOUND FOR TORCHES ≤ 15'	.078" - 3/32"	16.5'	.125"
415-332-258	HIGH CARBON STEEL - 'D' WOUND FOR TORCHES ≤ 25'	.078" - 3/32"	26.5'	.125"
415-332-166	3.35" EXTENSION - GALVANIZED STEEL - 'D' WOUND - 14' LONG HEAT SHRINK	.078" - 3/32"	16.5'	.125"
415-332-266	3.35" EXTENSION - GALVANIZED STEEL - 'D' WOUND - 19' LONG HEAT SHRINK	.078" - 3/32"	21.5'	.125"
415-332-167	GALVANIZED STEEL - 'D' WOUND - 14' LONG HEAT SHRINK	.078" - 3/32"	16.5'	.125"
415-332-267	GALVANIZED STEEL - 'D' WOUND - 19' LONG HEAT SHRINK	.078" - 3/32"	21.5'	.125"
615-18-154	HIGH CARBON STEEL - 'D' WOUND FOR 60XX AND 61XX SERIES TORCHES	7/64" - 1/8"	16.5'	.175"

