# Q-Gun<sup>®</sup> Series 200, 300, 400 Amp MIG Guns

**400 amp Q-Gun™ MIG Gun** shown with curved handle, medium 45° rotating neck and standard trigger.



Industrial Workhorse 200, 300 and 400 amp Q-Gun™ MIG Guns are easy-to-use and designed for

exceptional performance and comfort in the most demanding industrial environments.

#### Stay-Tite™ Technology

Long-lasting power cable compression fittings and necks with large tapered gun connections combine to form the foundation of Bernard Stay-Tite™ Technology. This technology ensures optimal conductivity to increase weld consistency and lessen heat output while improving product durability.

Q-Gun		Description			
	100% NEMA	100%CE	60% CE	35%CE	
Q200	250	200	240	325	CO <sub>2</sub> Gas
	n/a	175	200	240	80%AR20%CO <sub>2</sub>
Q300	350	320	370	470	CO <sub>2</sub> Gas
	n/a	270	310	390	80%AR20%CO <sub>2</sub>
Q400	400	350	425	520	CO <sub>2</sub> Gas
	n/a	285	350	440	80%AR20%CO <sub>2</sub>

Issued Jan. 2013 • Index No. SPEC Q234-1.4

## All Guns are Not Created Equal.

A MIG gun should be durable, easyto-use and customized to your specific application. Our MIG guns put you in control: you choose the options you need and we'll build a gun to last.

Centerfire™ Contact Tips, Nozzles and Diffusers are easy-to-use and high performing - they provide better arc starts, less spatter and more consistent welds - and also last up to three times longer than competitive brands.

Necks available in fixed, rotatable and multiple length options for optimal weld accessibility and improved operator comfort. Rotatable necks changeover without tools.

**Jump Liner** allows quick neck change and replacement of only most commonly worn or clogged liner area, which reduces the amount of time a gun is offline and minimizes inventory.

Multiple handle and trigger options to increase operator comfort.

Power cable equipped with Stay-Tite™

**Technology** and internal gas hose that resists kinking, improves gas flow and feedability.

**Back end with durable rigid strain relief** and easily interchangeable direct plugs and trigger leads connect to wire feeders and machines from major manufacturers and allow simple maintenance.




### Bernard

An Illinois Tool Works Company 449 West Corning Road, Box 667 Beecher, Illinois 60401 USA  $\begin{array}{l} \mbox{Phone: 800-946-2281 (US Only) 708-946-2281 (Outside US) } \\ \mbox{Fax: 708-946-6726} \\ \mbox{For more information, visit us at BernardWelds.com} \end{array}$ 



# **Replacement Parts List**



ITEM #	Q200 Part #	Q300 Part #	Q400 PART #	DESCRIPTION		
1	See Centerfire Spec Sheet			Nozzle Assy		
2	See Centerfire Spec Sheet			Contact Tip		
3	See	Centerfire Spec S	Gas Diffuser			
4	See	Centerfire Spec S	Сар			
5	S	ee Neck Spec She	Neck			
6	See	Jump Liner Spec	Jump Liner			
7	42	13B	4313B	Stay-Tite™ End Fitting		
8	4305		1540003	Stay-Tite™ Cone Nut		
NS	4991		1520017	Conduit Clamp (2 Req'd)		
NS	4823		4939	Jacket Clamp (2 Req'd)		
9	1880155		1880198	Handle Kit, Standard Locking*		
				Handle Kit, Locking Trigger*		
				Handle Kit, Dual Pull Trigger*		
	N	/A	DSA-1	Handle Kit, D/S, Std. Trigger*		
				Handle Kit, D/S, Locking Trigger*		
10	5662			Trigger, Standard		
		5662L		Trigger, Locking		
	2690001			Trigger, Dual Pull, 3 Wire <i>(With Insulated Terminals)</i>		
11	4207			Post Fastener <i>(1 Req'd - Q200 &amp; Q300)</i> <i>(5 Req'd - Q400)</i>		
	2030004 N/A			Post Fastener, Short (4 Req'd)		
12	4209			Handle Screw <i>(5 Req'd)</i>		
13	2660001			Terminal, Quick Disconnect (2 Req'd)		
14	N/A 2520042			Handle Spring		
15	1060120	1060108	1060114	8' (2.44 m)		
	1060121	1060109	1060115	10' (3.05 m)		
	1060122	1060110	1060116	12' (3.66 m)		
	1060123	1060111	1060117	15' (4.57 m)		
	1060124	1060112	1060118	20' (6.10 m)		
	1060125	1060113	1060119	25' (7.62 m)		
16	2520033 2520041		2520041	Strain Relief		
17			1	Rigid Strain Relief Kit (Includes: Top & Bottom Halves)		
	2520073			Strain Relief with Installed Gas Pin (Bernard Direct Plug)		
				Strain Relief <i>(Euro<sup>®</sup> Direct Plug)</i>		
	2520066			Strain Relief (All Other Direct Plugs)		
18		4932		Butt Connector (2 Req'd)		
19	See Direct Plug Spec Sheet			Direct Plug Components		
20	See Liner Spec Sheet			Liner		
21		1790002	Hang up Hook Kit (Includes: Hook, Screw, & Post)			
22	1982	1983Q	1984Q	Rear Stay-Tite™ Repair Kit <sup>†</sup>		
23	1010027		1	Adaptor Block (Not Req'd on Bernard or Euro <sup>®</sup> Direct Plug)		
24		2280056	Screw, Strain Relief (Not Req'd on Bernard Direct Plug)			
25	1620003			Screw Cover, Strain Relief		
26	GN2021			Electrical Plug-Non D/S ( <i>Not Req'd on</i> Bernard or Euro <sup>®</sup> Direct Plug)		
	20006A			Electrical Plug-D/S (Not Req'd on Bernard or Euro <sup>®</sup> Direct Plug)		

\*1880155 & 1880198 Handle Kits include halves, screws & posts. \*DSA-1 Handle Kits include halves, screws, posts, toggle switch and

"DSA-T Handle Kits include naives, screws, posts, toggle switch and guard.

<sup>†</sup>1982, 1983Q & 1984Q Rear Cone Nut Repair Kits include jacket clamp, conduit clamp, cone nut, end fitting, nipple, spacer & butt connectors.

Bernard<sup>™</sup> is a trademark of Illinois Tool Works Inc. Other brands mentioned are for reference only and are the registered trademarks of their respective companies, and are not affiliated with Illinois Tool Works Inc.

