



Tregaskiss® TOUGH GUN® G2 Series Robotic Air-Cooled MIG Gun

TOUGH GUN G2 Series			Amperage	Neck	Option 1	Option 2	Cable Length	Nozzle	Contact Tip*	Wire Size	Power Pin
R	A	2	5	A	C	1	A	B	1	B	M
			3 300 amp 5 500 amp	<i>Air-Cooled</i> 22 Degrees	C Clutch S Solid Mount	0 No options 1 Wire brake	A 3.0 ft B 3.5 ft C 4.0 ft D 4.5 ft E 5.0 ft F 5.5 ft G 6.0 ft H 6.5 ft J 7.0 ft K 7.5 ft L 8.0 ft M 8.5 ft N 9.0 ft P 9.5 ft R 10.0 ft S 10.5 ft T 11.0 ft U 12.0 ft V 13.0 ft W 14.0 ft Y 15.0 ft	A 401-6-62 B 401-81-62 C 401-4-62 D 401-8-62 E 401-42-50 F 401-48-50 G 401-48-62 H 401-44-50 J 401-49-50 K 401-71-62 M 401-87-62 N 401-44-62 P 401-91-62 Q 401-56-62 R 401-54-50	1 403-20-XX 2 403-21-XX 4 403-27-XX	B 0.030" C 0.035" D 1.0 mm E 0.045" F 3/64" G 0.052" J 1/16" <u>Aluminum</u> R 0.035" S 3/64" T 1/16"	D OTC Daihen® E Euro F Fronius® L Lincoln® M Miller® P Panasonic® C L-Tec® Euro T Tweco #4 W Tweco #5 <u>AutoLength™ Pin**</u> 1 Tweco #4 2 Lincoln 3 Tweco #5 4 Miller 5 Euro 7 Fronius
				A 22 J 22L K 22L1 35 Degrees B 35 45 Degrees D 45L L 45L1 M 45L2 <u>TOUGH GUN I.C.E.™</u> E 22 degrees F 35 degrees H 45 degrees							

*XX = wire size

**Not compatible with wire brake option

IMPORTANT NOTE:

This document is no longer updated or maintained, and is for reference only.